

## PMR205AB6100M100R30

## Aliases (P405QE104M125AH101)

PMR205/P405, Film, Metallized Paper, Resistor/Capacitor, 0.1 uF, 20%, 250 VDC, 85°C, Lead Spacing = 15.2mm



Click here for the 3D model.

Dimensions	
L	18.5mm MAX
н	10.5mm MAX
т	5.2mm MAX
S	15.2mm +/-0.4mm
LL	30mm +5mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Deeleasing	

	Bag
Packaging Quantity 500	

General Information	
Series	PMR205/P405
Dielectric	Metallized Paper
Style	Radial
Features	RC Unit not approved
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Construction	Molded
Component Weight	1.53 g
Miscellaneous	Resistor Tolerance: +/-30%. Resistor= 100 Ohms.

Specifications			
Capacitance	0.1 uF		
Capacitance Tolerance	20%		
Voltage AC	125 VAC		
Voltage DC	250 VDC		
Temperature Range	-40/+85°C		
Rated Temperature	85°C		
Insulation Resistance	3 GOhms		
Safety Class	X2		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.