




HYPERBUSS AT 12WAY RECP.(3)4 PIN BUSBAR NI-PLATED







REFER TO SHEET 2 FOR


AVAILABLE CONNECTOR COLORS

NOTES: UNLESS OTHERWISE SPECIFIED

⚠ SEE SHEET 2 FOR KEY ARRANGEMENTS AND COLORS.

2. MATERIAL:
HOUSING: THERMOPLASTIC
SEAL:SILICONE RUBBER
CONTACT:COPPER ALLOY

- 3. MODIFICATIONS: 3 PIECES OF 4 PIN BUSBAR WITH NICKEL PLATED
- 4. SPECIFICATIONS:
 - 4.1 CURRENT RATING: 26 AMPS MAXIMUM FOR THE 4 PIN BUSBAR
 - 4.2 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 4.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 4.4 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 4.5 MOISTURE RESISTANCE: IP69K & IP68
 - (1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION)
 - 4.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 4.7 RoHS COMPLIANT
- 5. MATING PART: AT06-12SX* PLUG (X=A,B,C,D KEYS * = AVAILABLE MODIFICATIONS)
- ORIENTATION OF "Amphenol" AND "-P075" TO BE OPTIONAL
- BORDERS SIGINIFY THAT EACH GROUP OF PINS (PINS 1,2,11,12 AND PINS 3,4,9,10 AND PINS 5,6,7,8) ARE BUSSED TOGETHER WITH A 4 PIN BUSBAR
- 8. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.




				075 REV: A3		
				SH:		
	SEE SHEET 2	REF: DT04-12PA-P075 & DT04-12PB-P075 & DT04-12PC-P075 & DT04-12PD-P075		유		
ļ		DECODIFICAL.				

END CAP

	PART N	PART NUMBER		DESCRIPTION			ITEM	
QUANTITY		MATERIALS LIST						
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm).		SIGNATUR	ES DATE	A manhanal				
2) Tolerances are		DRAWN: RONALD	11NOV21	Amphenol				
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED: ORION	12NOV21	s	Sine Systems - www.amphenol-sine.com			
3) Note reference = X MATERIAL SPECIFICATIONS:		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036				
		APPROVAL: TOMMY	15NOV21	Cilitori Township, Wii 46030				
WEIGHT:	27.6g	CUSTOMER: THIS DRAWING IS SUPPLIED FOR		–	RBUSS AT 12WAY F PIN BUSBAR NICKI		E	
PROCESS SPECIFICATIONS: NEXT ASS'Y:		INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION, NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SHE INCT TO NORMAL		SIZE TYPE DWG NO:			A3	

		REVISIONS							
REV		ECO DESCRIPTION		DATE	BY	APPR			
	A1	-	RELEASE NEW DRAWING	11APR18	ROOKIE	TOMMY			
	A2	-	REVISED DESCRIPTION	12JUN19	JAH	DH			
	A3	-	UPDATE THE APPEARANCE	11NOV21	RONALD	TOMMY			

P/N AT04-12PA-P075 **KEY-A CONFIGURATION** STANDARD COLOR: GREY




P/N AT04-12PB-P075


KEY-B CONFIGURATION

STANDARD COLOR: BLACK

P/N AT04-12PC-P075 **KEY-C CONFIGURATION** STANDARD COLOR: GREEN



P/N AT04-12PD-P075 **KEY-D CONFIGURATION** STANDARD COLOR: BROWN



	PART NUMBER		DESCRIPTION			ITEM	~	
QUANTITY	MATERIALS LIST							
1) All dimensions a	WISE SPECIFIED SIGNATI		S DATE	Amphenol				
2) Tolerances are a	as follows: Fractions ±1/64 Angles ±1°	DRAWN: RONALD	11NOV21					
2 PL DEC ±0.30 3 PL DEC ±0.08		CHECKED: ORION	12NOV21	Sine Systems - www.amphenol-sine.com			_	
3) Note reference		ENGINEER:		44724 Morley Drive				
MATERIAL SPECIFICATIONS:		APPROVAL: TOMMY	15NOV21	Clinton Township, MI 48036				-
WEIGHT:	27.6~	CUSTOMER:	•		RECEPTACLE			
		THIS DRAWING IS SUPPLIED FOR		(3)4 PIN BUSBAR NICKEL-PLATED				
PROCESS SPECIFICATIONS: NEXT ASS'Y:		SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		B C-	AT04-12PX		A3	
				SCALE: NONE		sheet 2 of	2	1

AT04-12PX-P075 REV: A3 SH:

HYPERBUSS AT 12WAY RECP.(3)4 PIN BUSBAR NI-PLATED