

	ELECTRICAL DATA:								
TESTS	CONDITIONS	ACCEPTANCE CRITERIA							
Sec. N.L.V	@ 240V, 60Hz, TER 1 - TER 2								
	WHT - WHT	2046.0 V ±3%							
POLARITY									
DCR	TER 1 - TER 2	0.056 ±20%							
IN OHMS	WHT - WHT	3.24 ±20%							
HIPOT									
	PRMARY - CORE	2000V, 60Hz, 1 SEC							
	SECONDARY - CORE	5000V, 60Hz, 1 SEC							
	PRMARY - SECONDARY	5000V, 60Hz, 1 SEC							
	1	l							

## LABEL:



WHT =

PROPERTY AND COPYRIGHT NOTICE

LABEL

10.00"

**GRN** 

THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED,

	TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING.											
RE	NOTES	BY	DATE	REV	NOTES	BY	DATE	ATT HAMMO MANUFA		ELECTRONIC DIVISION 52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5 PHONE: 519.886.6181 FAX: 519.886.9540		
								5KVA POWER TRANSFORMER				
								C. BACIK	05/08/1 DATE	PWDP13059		
	•	•								•		