

US1A-M

SURFACE MOUNT ULTRAFAST EFFICIENT RECTIFIER

Reverse Voltage - 50 to 1000 Volts

Forward Current - 1.0 Ampere

Features

- Plastic package has Underwriters Laboratory
- Flammability Classification 94V-0
- Glass passivated chip junctions
- Ultrafast recovery times for high efficiency
- Low forward voltage, low power loss
- High temperature soldering guaranteed:
- 260°C/10 seconds on terminals
- RoHS compliant package

Mechanical Data


- Case: JEDEC DO-214AC molded plastic body
- Terminals: Solder plated, solderable per

MIL-STD-750, Method 2026

- Polarity: Color band denotes cathode end
- Weight: 0.063 gram


Packing & Order Information

5,000/Reel




RoHS
COMPLIANT

SMA (DO-214AC)



Dimensions in millimeters

Graphic symbol



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

		US1A	US1B	US1D	US1G	US1J	US1K	US1M	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RWS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	100	V
Maximum average forward rectified current at $T_L=110^\circ\text{C}$	$I_{F(AV)}$	1							A
Peak forward surge current 8.3ms single half-sine-wave	I_{FSM}	30							A

US1A-M

SURFACE MOUNT ULTRAFAST EFFICIENT RECTIFIER

Ratings at 25°C ambient temperature unless otherwise specified


		US1A	US1B	US1D	US1G	US1J	US1K	US1M	UNITS
Maximum instantaneous forward voltage at $I_{FM}=2.0A$	V_F	1.0			1.4	1.7			V
Maximum DC reverse current $T_J=25^\circ C$ At rated DC blocking voltage $T_A=100^\circ C$	I_R				10 50				μA
Maximum reverse recovery time	T_{rr}	50					75		nS
Typical junction capacitance	C_j	17					15		pF
Maximum thermal resistance	$R_{\theta JA}$				35				$^\circ C/W$
	$R_{\theta JL}$				27				$^\circ C/W$
Storage temperature range	T_{STG}				-55 to +150				$^\circ C$

NOTE : 1.Pulse test: Pulse width 300us, duty cycle 1%

US1A-M

SURFACE MOUNT ULTRAFAST EFFICIENT RECTIFIER

■ Ratings and Characteristic Curves



US1A-M

SURFACE MOUNT ULTRAFAST EFFICIENT RECTIFIER

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE. Bruckewell Technology Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Bruckewell"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Bruckewell makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Bruckewell disclaims

- (i) Any and all liability arising out of the application or use of any product.
- (ii) Any and all liability, including without limitation special, consequential or incidental damages.
- (iii) Any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Bruckewell's knowledge of typical requirements that are often placed on Bruckewell products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time.

Product specifications do not expand or otherwise modify Bruckewell's terms and conditions of purchase, including but not limited to the warranty expressed therein.