

ENGINEERING	PRODUCT SPECIFICATION	SPEC.NO.: SPCH091A
DEPT.	For 2.54x2.54 mm (.100"x.100") Board to Board Connectors of System CH88	PAGE: 1/3

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202	Methods for test of connectors for electronic equipment
EIA 364	Test methods for electrical connectors
J-STD-020	Resistance to soldering Temperature for through hole Mounted Devices
SS-00254	Test methods for electronic components ,LEAD-FREE soldering Part design standards

3. APPLICABLE SERIES NO.: CH88***A100-B / CH88***B100-B
CH88***C100-B / CH88***D100-B

4. SHAPE,CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

0.8 mm (.031") ~ 1.6 mm (.063")



REVIEWED : Eisley APPROVED : Sun VERIFIED : Sandy .



ENGINEERING DEPT.	PRODUCT SPECIFICATION For 2.54x2.54 mm (.100"x.100") Board to Board Connectors of System CH88	SPEC.NO.: SPCH091A
		PAGE: 2/3

7. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		3A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. 100 mA max.	Less than 20 mΩ
7.3	Dielectric strength	When applied AC 1000 V 1 minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 5000 MΩ

8. MECHANICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Pin retention force	Apply axial pull out force at 25 ± 3mm/min on the assembly in the housing	More than 1 Kgf

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Cold Resistance	-40 °C ± 3 °C, 96 hours	Appearance: No damage Contact resistance: Δ20 mΩ change
9.2	Heat Resistance	105 °C ± 3 °C, 96 hours	Appearance: No damage Contact resistance: Δ20 mΩ change
9.3	Temperature Cycling	5 cycles (1) -40 °C , 30 min. (2) Room temp. 10-15 min. (3) 105 °C , 30 min. (4) Room temp. 10-15 min.	Appearance: No damage Contact resistance: Δ20 mΩ change
9.4	Humidity	40±2 °C , 90-95% RH, 96 hours Measurement must be taken within 30 min. After tested	Appearance: No damage Contact resistance: Less than twice of initial



ENGINEERING DEPT.	PRODUCT SPECIFICATION For 2.54x2.54 mm (.100"x.100") Board to Board Connectors of System CH88	SPEC.NO.: SPCH091A
		PAGE: 3/3

	ITEM	TEST CONDITION	REQUIREMENT
9.4	Salt Spray	Temperature: $35 \pm 2^{\circ}\text{C}$ Solution: $5 \pm 1\%$ Spray time: 6 ± 1 hours Measurement must be taken after water rinse	Appearance: No damage Contact resistance: $\Delta 20 \text{ m}\Omega$ max out.
9.5	Solder ability	Soldering time: 3 ± 0.5 sec Soldering pot: $230 \pm 5^{\circ}\text{C}$	Minimum: 90% of immersed area
9.6	Resistance to soldering heat	Soldering time: 5 ± 0.5 sec Soldering pot: $260 \pm 5^{\circ}\text{C}$	No damage

10. OPERATING TEMPERATURE : -40°C to $+105^{\circ}\text{C}$