

RESISTANCE @ $+25^{\circ}C = 5 \Omega \pm 20^{\%}$ MAXIMUM STEADY STATE CURRENT (Imax) = 8 AMPS

RESISTANCE @ Imax = 0.070Ω NOMINAL

DIM "D" = 1.150" MAXIMUM

DIM "T" = 0.350" MAXIMUM

DIM "L" = 0.700" MINIMUM

DIM "S" = 0.395" NOMINAL

LEAD WIRE DIAMETER = 0.040" NOMINAL DIAMETER

*** ROHS COMPLIANT ***

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"A"	MAXIMUM DIAMETER WAS 0.600", DIM "L" WAS 1" MINIMUM, DIM "S" WAS 0.310" NOMINAL & DIM "T" WAS 0.250" MAXIMUM	10/30/12	DD
NONE	RELEASE TO PRODUCTION	07/27/11	DD
REV	REVISION RECORD	DATE	APP

DIM ''T''

SCALE NONE	C COPYRIGHT
DRAWN BY DAN DANKERT	U.S. SENSOR CORP.
DATE 05/20/95	714-639-1000 www.ussensor.com
REV. "A"	INRUSH CURRENT LIMITER
LAYER 0 OF 2	P/N ST5R008B