



ALPHA & OMEGA
SEMICONDUCTOR

AOTF42S60

600V 39A α MOS™ Power Transistor

General Description

The AOTF42S60 has been fabricated using the advanced α MOS™ high voltage process that is designed to deliver high levels of performance and robustness in switching applications. By providing low $R_{DS(on)}$, Q_g and E_{OSS} along with guaranteed avalanche capability this device can be adopted quickly into new and existing offline power supply designs.

Product Summary


| | |
|----------------------|--------|
| $V_{DS} @ T_{j,max}$ | 700V |
| I_{DM} | 166A |
| $R_{DS(ON),max}$ | 0.099Ω |
| $Q_{g,typ}$ | 40nC |
| $E_{oss} @ 400V$ | 9.2μJ |

100% UIS Tested
100% R_g Tested




Top View

TO-220F



AOTF42S60



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Parameter | Symbol | AOTF42S60 | AOTF42S60L | Units |
|---|----------------|------------|------------|-------|
| Drain-Source Voltage | V_{DS} | 600 | | V |
| Gate-Source Voltage | V_{GS} | ± 30 | | V |
| Continuous Drain Current | I_D | 39* | 39* | A |
| $T_c=100^\circ\text{C}$ | | 25* | 25* | |
| Pulsed Drain Current ^C | I_{DM} | 166 | | |
| Avalanche Current ^C | I_{AR} | 11 | | A |
| Repetitive avalanche energy ^C | E_{AR} | 234 | | mJ |
| Single pulsed avalanche energy ^G | E_{AS} | 1345 | | mJ |
| Power Dissipation ^B | P_D | 50 | 37.9 | W |
| Derate above 25°C | | 0.4 | 0.3 | W/°C |
| MOSFET dv/dt ruggedness | dv/dt | 100 | | V/ns |
| Peak diode recovery dv/dt ^H | | 20 | | |
| Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | | °C |
| Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds ^J | T_L | 300 | | °C |
| Thermal Characteristics | | | | |
| Parameter | Symbol | AOTF42S60 | AOTF42S60L | Units |
| Maximum Junction-to-Ambient ^{A,D} | R_{0JA} | 65 | 65 | °C/W |
| Maximum Junction-to-Case | R_{0JC} | 2.5 | 3.3 | °C/W |

* Drain current limited by maximum junction temperature.

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|-----------------------------|---|---|-----|-------|-------|-------|
| STATIC PARAMETERS | | | | | | |
| BV _{DSS} | Drain-Source Breakdown Voltage | I _D =250μA, V _{GS} =0V, T _J =25°C | 600 | - | - | V |
| | | I _D =250μA, V _{GS} =0V, T _J =150°C | 650 | 700 | - | |
| I _{DS} | Zero Gate Voltage Drain Current | V _{DS} =600V, V _{GS} =0V | - | - | 1 | μA |
| | | V _{DS} =480V, T _J =150°C | - | 10 | - | |
| I _{GSS} | Gate-Body leakage current | V _{DS} =0V, V _{GS} =±30V | - | - | ±100 | nA |
| V _{GS(th)} | Gate Threshold Voltage | V _{DS} =5V, I _D =250μA | 2.5 | 3.2 | 3.8 | V |
| R _{DS(ON)} | Static Drain-Source On-Resistance | V _{GS} =10V, I _D =21A, T _J =25°C | - | 0.085 | 0.099 | Ω |
| | | V _{GS} =10V, I _D =21A, T _J =150°C | - | 0.24 | 0.28 | Ω |
| V _{SD} | Diode Forward Voltage | I _S =21A, V _{GS} =0V, T _J =25°C | - | 0.84 | - | V |
| I _S | Maximum Body-Diode Continuous Current | | - | - | 39 | A |
| I _{SM} | Maximum Body-Diode Pulsed Current | | - | - | 166 | A |
| DYNAMIC PARAMETERS | | | | | | |
| C _{iss} | Input Capacitance | V _{GS} =0V, V _{DS} =100V, f=1MHz | - | 2154 | - | pF |
| C _{oss} | Output Capacitance | | - | 135 | - | pF |
| C _{o(er)} | Effective output capacitance, energy related ^H | V _{GS} =0V, V _{DS} =0 to 480V, f=1MHz | - | 103 | - | pF |
| C _{o(tr)} | Effective output capacitance, time related ^I | | - | 344 | - | pF |
| C _{rss} | Reverse Transfer Capacitance | V _{GS} =0V, V _{DS} =100V, f=1MHz | - | 2.7 | - | pF |
| R _g | Gate resistance | V _{GS} =0V, V _{DS} =0V, f=1MHz | - | 1.7 | - | Ω |
| SWITCHING PARAMETERS | | | | | | |
| Q _g | Total Gate Charge | V _{GS} =10V, V _{DS} =480V, I _D =21A | - | 40 | - | nC |
| Q _{gs} | Gate Source Charge | | - | 11.7 | - | nC |
| Q _{gd} | Gate Drain Charge | | - | 11.9 | - | nC |
| t _{D(on)} | Turn-On Delay Time | V _{GS} =10V, V _{DS} =400V, I _D =21A, R _G =25Ω | - | 38.5 | - | ns |
| t _r | Turn-On Rise Time | | - | 53 | - | ns |
| t _{D(off)} | Turn-Off Delay Time | | - | 136 | - | ns |
| t _f | Turn-Off Fall Time | | - | 46 | - | ns |
| t _{rr} | Body Diode Reverse Recovery Time | I _F =21A, dI/dt=100A/μs, V _{DS} =400V | - | 473 | - | ns |
| I _{rm} | Peak Reverse Recovery Current | I _F =21A, dI/dt=100A/μs, V _{DS} =400V | - | 38.5 | - | A |
| Q _{rr} | Body Diode Reverse Recovery Charge | I _F =21A, dI/dt=100A/μs, V _{DS} =400V | - | 10.5 | - | μC |

A. The value of R_{0JA} is measured with the device in a still air environment with T_A=25° C.

B. The power dissipation P_D is based on T_{J(MAX)}=150° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150° C. Ratings are based on low frequency and duty cycles to keep initial T_J=25° C.

D. The R_{0JA} is the sum of the thermal impedance from junction to case R_{0JC} and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300 μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T_{J(MAX)}=150° C. The SOA curve provides a single pulse rating.







G. L=60mH, I_{AS}=6.7A, V_{DD}=150V, Starting T_J=25° C







H. C_{o(er)} is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% V_{(BR)DSS}.





I. C_{o(tr)} is a fixed capacitance that gives the same charging time as C_{oss}, while V_{DS} is rising from 0 to 80% V_{(BR)DSS}.




APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:
http://www.aosmd.com/terms_and_conditions_of_sale

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS


TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 7: Body-Diode Characteristics (Note E)

Figure 8: Gate-Charge Characteristics

Figure 9: Capacitance Characteristics

Figure 10: Coss stored Energy

Figure 11: Maximum Forward Biased Safe Operating Area for AOTF42S60 (Note F)

Figure 12: Maximum Forward Biased Safe Operating Area for AOTF42S60L (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 13: Avalanche energy

Figure 14: Current De-rating (Note B)

Figure 15: Normalized Maximum Transient Thermal Impedance for AOTF42S60 (Note F)

Figure 16: Normalized Maximum Transient Thermal Impedance for AOTF42S60L (Note F)

Gate Charge Test Circuit & Waveform

Resistive Switching Test Circuit & Waveforms

Unclamped Inductive Switching (UIS) Test Circuit & Waveforms

Diode Recovery Test Circuit & Waveforms
