



示意图 SCHEMATIC

规格 Specifications

额定负荷 Ratings	DC 16 V 0.1 A
初期接触电阻 Initial Contact Resistance	40 m ΩMax.
绝缘电阻 Insulation Resistance	DC250V 60Sec.100M ΩMin.
抗电强度 Dielectric Voltage	AC 250 V(50~60HZ) 60_Sec.

操作力 Operating Force(gf)	30±15 gf
负荷寿命 Operating Life With Load	20,000 次 Cycles

05	端子B TERMINAL B	C5210R	1	Ag CLAD	A02	增加尺寸标注, 见 ⑤	刘 斌	2012-4-12
04	端子A TERMINAL A	C5210R	1	Ag CLAD	A01	增加规格栏见 ①	曹文斌	06-03-27
03	杠杆 LEVER	POM	1	NATURAL		材料C5210R-EH变更为C5210R标示见 ①		
02	胶壳 CASE	PBT	1	NATURAL	01		赖立辉	29 JUN 00
01	胶盖 COVER	PC	1	NATURAL	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO. ITEM1803			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	DETECTOR SWITCH		ITEM NO	DS-040-02		
UNDER 1	± 0.10	DRAWN	刘 斌	2012-4-12	VERSION	A02	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	王光云	2012-4-12	SCALE	—	UNIT	mm
OVER 10	± 0.50	APPROVED	方 勇	2012-4-12	PROJECTION			

COMAX 高铭电子(惠州)有限公司
Comax Electronics(Huizhou)Co.,Ltd.