

Title of Change:	Final PCN for wafer fabrication site transfer to ON Semiconductor Niigata Co., Ltd. In Niigata, Japan (Group KC)			
Proposed first ship date:	9 November 2017 or earlier upon customer approval			
Contact information:	Contact your local ON Semiconductor Sales Office or <yasunari.noguchi@onsemi.com></yasunari.noguchi@onsemi.com>			
Samples:	Contact your local ON Semiconductor Sales Office			
Additional Reliability Data:	Contact your local ON Semiconductor Sales Office or <yasuhiro.igarashi@onsemi.com>.</yasuhiro.igarashi@onsemi.com>			
Type of notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <pcn.support@onsemi.com>.</pcn.support@onsemi.com>			
Change Part Identification:	Affected products will be identified with date code.			
Change category:	Wafer Fab Change Assembly Change Test Change Other			
Change Sub-Category(s): Manufacturing Site Change/ Manufacturing Process Char Sites Affected: All site(s) ont ag				
ON Niigata, Japan				
Description and Purpose:				
This is a Final Process Change Notification to announce the transfer to a new wafer fabrication site for the device covered in this notice. Device formerly manufactured at the Manufacturers AMPI will be manufactured at ON Semiconductor Niigata Co., Ltd. (OSNC) following the expiration of this notice. OSNC located in Niigata, Japan has obtained ISO9001 certification.				
The product design and electrical specifications will remain identical. A full electrical characterization over the temperature range will be performed to check the device functionality and electrical specifications.				



Reliability Data Summary:

QV DEVICE NAME: SFT1443-TL-W PACKAGE: TP-FA

Test	Specification	Condition	Interval	Result
HTRB	JESD22-A108	Ta=150°C, 80% max rated VDSS	1008 hrs	0/231
HTGB	JESD22-A108	Ta=150°C, 100% max rated VGSS	1008 hrs	0/231
SSOL	JESD22-A108	Tj= 150°C	1008 hrs	0/75
AC	JESD22-A102	Ta = 121°C, 100% RH, 15psig	96 hrs	0/231
TC	JESD22-A104	Ta= -55°C to +150°C	100 cyc	0/75
HAST	JESD22-A110	130°C, 85% RH, 18.8psig, 80% max rated VDSS	96 hrs	0/231
PC	J-STD-020 JESD-A113	MSL 1 @ 260°C	-	-
RSH	JESD22- B106	Ta = 265°C, 10 sec	-	0/90

Electrical Characteristic Summary:

Electrical characteristics are not impacted.

List of affected Standard Parts:

Part Number	Qualification Vehicle
SFT1443-TL-W	SFT1443-TL-W