



## EXS

### Two-Way Radio Antenna

Laird's in-building wireless antennas are particularly applicable in environments where aesthetics and wide-angle coverage are necessary for successful wireless deployment. Because of their small size, you can hide the antenna almost anywhere, providing an invisible solution for most applications.

External antennas are weather resistant and waterproof high-gain antennas that provide an excellent choice for outdoor and indoor installation, and can be mounted on the outside of a housing. These antennas are designed for maximum efficiency and are customizable and scalable to meet your frequency and application requirements.

### FEATURES AND BENEFITS

- Injection-molded ¼ wave helical slim mini antenna
- High durability, high efficiency
- Textured finish with strain-relief base
- An original Tuf Duck antenna

### MARKETS

- Public safety/Two-way
- Trunking/Cellular
- For Bluetooth and IEEE 802.11BG devices

#### SPECIFICATION

Operating Frequency (MHz)	VHF Trunking/Cellular
VSWR - Max	1.5:1 max at resonance
Nominal Impedance (Ohms)	50
Power Handling (W)	50
Polarization	Vertical
Operating Temperature - °C (°F)	-40 (-40) to +85 (+185)
Drop Test	1 meter

## CONFIGURATION

The EXS model antenna is available in the following frequencies and connectors. Order by antenna model, frequency, and connector.

For example: EXS150MX. Length of each antenna varies with the chosen connector.

PART NUMBER	FREQUENCY BAND	CONNECTOR	AVERAGE LENGTH
EXS000	Untuned	MX, SF, SFU, SM, SMI	4.0" -5"
EXS118	118-127 MHz	BNX	5.1"
EXS136	136-144 MHz	MX, SF, SMI	3.62" - 4.4"
EXS144	144-148 MHz		3.55" - 4.45"
EXS148	150-162 MHz	MX, SF	3.50"
EXS150	150-164 MHz	BN, BNX, MD, MX, MXI, SF, SFU, SMI, SMV, TNX	3.5" - 4.39"
EXS155	155-164 MHz	MX, SF, SFU, SMI, TNX	3.45" - 4.2"
EXS164	164-174 MHz	BN, MX, SFU, SMI, TNX	3.3" - 3.95"
EXS220	220-225 MHz	MX	3.0"
EXS806	806-866 MHz	SF, SFU, SM	1.83"
EXS880/1710	880-1710 MHz	SM	2.75"
EXS902	896-941 MHz	SFU	1.89"
EXSN2.4HW	2.4 GHz	RSM	N/A

### TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

### te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original