

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


© 2005, Projects Unlimited Inc.


## **SPECIFICATIONS**

PARAMETERS	VALUES	UNITS	
RATED INPUT POWER	0.3	W	
MAX INPUT POWER	0.5	W	
IMPEDANCE	25±15%	ОНМ	
OUTPUT SPL @ 0.1W/0.1M (AT 0.8, 1.0, 1.2, 1.5 kHz)	86±3	dBA	
DISTORTION (MAX.)	5%	_	
RESONANT FREQUENCY	850±20%	Hz	
FREQUENCY RANGE	Fo ~ 20,000	Hz	
HOUSING MATERIAL	PBT	_	
CONE MATERIAL	MYLAR	_	
MAGNET MATERIAL	NdFeB	_	
OPERATING TEMPERATURE	−30 ~ +70	<b>°</b> C	
WEIGHT	1.5	grams	










## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2011/65/EU COMPLIANT.

AS01525MR-R.DWG



3541 Stop Eight Road Dayton, Ohio 45414

APPI	ROVALS	DATE	SPEAKER						
DRAWN	A.4. /	1 /15	SIZE DRAWING NO.						
	M.L.	1/15							
CHECKED	M.L.	1/15	Α	Α	S01525MR-R	₹			
APPROVED	B.R.	1/15	SCALE	: N.T.S.	SH	HEET	1	OF	1