## 9001KM38

Harmony 9001K, Harmony 9001SK, light block, 30mm, incandescent bulb, 120V





Main		
Range of Product	Harmony 9001K Harmony 9001SK	
Product or Component Type	Light block	
Device short name	9001K	
Bulb base	BA 9s	
Light block supply	Direct via integral resistance	

#### Complementary

Net Weight	0.11 lb(US) (0.05 kg)	
Light source	Incandescent bulb	
[Us] rated supply voltage	120 V AC/DC	
Light block supply	Full voltage or resistor	
Size	30 mm	

#### **Environment**

Environment	
Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-4 EN/IEC 60947-1 CSA C22.2 No 14 JIS C 852 JIS C 4520
Product Certifications	NEMA UL 508
Electrical shock protection class	Class II IEC 61140
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

#### Ordering and shipping details

Category	21435-9001 KM LIGHT MODULES	
Discount Schedule	CS1	
GTIN	3389110918557	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.24 oz (63.503 g)	
Returnability	Yes	
Country of origin	MX	

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.20 in (5.588 cm)
Package 1 width	3.70 in (9.398 cm)
Package 1 Length	1.80 in (4.572 cm)

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.


#### Contractual warranty

Warranty	18 months

# Product data sheet Dimensions Drawings

# 9001KM38

#### **Dimensions**



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.